








Magnetic drill

ECO.32



Key specifications

Cutters	Twistdrills	Countersink	
			
32 mm	13 mm	40 mm	
1 1/4"	1/2"	1 9/16"	
Weight	Motor	Magnet	Stroke
			
12 kg	1000 W	1500 kg	150 mm
26.5 lbs	9.1 A	3300 lbs	5 15/16"

Technical data

	Metric	Imperial
Annular cutter	Ø 32 mm	Ø 1 1/4"
Twist drill	Ø 13 mm	Ø 1/2"
Countersinking	Ø 40 mm	Ø 1 9/16"
Length	320 mm	12 5/8"
Width	210 mm	8 1/4"
Height	370 - 512 mm	14 9/16" - 20 3/16"
Stroke	150 mm	5 15/16"
Weight	12 kg	26.5 lbs
Magnet (lwxh)	160x80x42 mm	6 5/16"x3 1/8"x1 5/8"
Magnetic force	1500 kg	3300 lbs
Motor power	1000 W	9.1 A
Speed (no load)	775 min ⁻¹	775 rpm
Speed (load)	440 min ⁻¹	440 rpm
	(1000W)	(9.1 A)
Spindle (Weldon)	19,05 mm	3/4"
Power supply	110 - 120 V AC / 50-60 Hz	
	220 - 240 V AC / 50-60 Hz	

Additional benefits:

- **Single speed gearbox**
- **Compact design**
- **Detachable spindle**
- **Practical long stroke**
- **Clear and easy controls**