



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H61 VALUE

PRESSURE

150÷200

bar

FLOW RATE

800÷1150

l/h

ABSORBED POWER

5÷6,4

kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ MAINTENANCE CHECK LED - MCL



PW-H61 VALUE

PW-H61/4 VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™ ADVANCED MULTIFUNCTION SAFETY CONTROLS



DIAD DIRECT INJECTION DETERGENT AND ANTI-SCALE



CIRCULAR DESIGN & OPERATION



G6000™ CERAMIC HIGH-TECH GUN



ALL TERRAIN



MODERN MODULAR BUILD UP



IPC'S EXCLUSIVE BOILER



IPC PUMP

SPECS



CONTROL PANEL WITH INDICATOR LAMPS.



USER FRIENDLY ACCESS TO ADJUSTMENT AND LIQUID REFILLING



NEW AND MORE RESISTANT PLASTIC.






TECHNICAL DATA

		PW-H61 D1813P4 T	PW-H61 D1915P4 T	PW-H61 D1517P4 RT	PW-H61 D1719P4 T	PW-H61 D2017P4 T
3 WHEELS						
Code		IDAC41361	IDAC41362	IDAC41377	IDAC41364	IDAC41363
4 WHEELS						
Code		PW-H61/4 D1813P4 T	PW-H61/4 D1915P4 T	PW-H61/4 D1517P4 RT	PW-H61/4 D1719P4 T	PW-H61/4 D2017P4 T
Code		IDAC41365	IDAC41366	IDAC41381	IDAC41368	IDAC41367
PERFORMANCE						
Operating pressure	bar/Mpa	30-180/3-18	30-190/3-19	30-150/3-19	30-170/3-17	30-200/3-20
Flow rate	l/h	450-800	450-900	500-1000	600-1150	500-1000
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	3-400-50/9,7	3-400-50/10,6	3-400-50/10,6	3-400-50/13,2	3-400-50/13,2
Absorbed power	kW	5	5	5	6,4	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	70	70	≥70	≥70
Fuel consumption	kg/h	5,8	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	120	122	122	140	140

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR40087 EXTENSION P70 - INOX	CODE: UGLN49986 H.P. NOZZLE 1/4 1504 (FOR 1813)	CODE: UGLN05200 H.P. NOZZLE 1/4 1505 (FOR 1517)	CODE: UGLN49987 H.P. NOZZLE 1/4 15045 (FOR 1915/2017)
				
CODE: UGLN49994 H.P. NOZZLE 1/4 2506 (FOR 1719)	CODE: - ANTI-SCALE TREATMENT M421 1 Kg	CODE: TBAP40308 HIGH PRESSURE HOSE 10 m (FOR 1813/1915)	CODE: TBAP40309 HIGH PRESSURE HOSE 10 m (FOR 1517/1719/2017)	
				

OPTIONAL ACCESSORIES

CODE: SPID24939 FIXED HYDROBRUSH LANCE P70	CODE: LCLC41140 LANCE FOR WASHING FLOORS INOX	CODE: LCLC49492 LANCE FOR WASHING FLOORS Ø 0,35 (FOR 1915)	CODE: LCLC49494 LANCE FOR WASHING FLOORS Ø 0,55 (FOR 1719)	CODE: LCLC49493 LANCE FOR WASHING FLOORS Ø 0,45 (FOR 1813/1517/2017)
				
CODE: KTRI40235 HOSE REEL KIT	CODE: RCIN10810 HOSE COUPLING M22	CODE: TBAP23853 DRAIN KIT 10 m	CODE: LCPR40104 EXTENSIO P70 + TPR255 Ø 0,35 (FOR 1310/1813)	CODE: LCPR40135 EXTENSIO P70 + TPR255 Ø 0,45 (FOR 1517/1915/2017)
				
CODE: LCPR14859 SANDBLASTER KIT Ø 1,5 mm (FOR 1517/1915/2017)	CODE: LCPR14858 SANDBLASTER KIT Ø 1,4 mm (FOR 1813)	CODE: LCPR13557 SANDBLASTER KIT Ø 1,6 mm (FOR 1719)	CODE: PRCH40041 SAND BAG 25 Kg	CODE: PRCH40039 ANTI-SCALE TREATMENT M421 1 Kg X 6
				
CODE: PRCH40040 ANTI-SCALE TREATMENT M421 10 Kg	CODE: KTRI40314 MAINTENANCE KIT 500H (FOR 1813/1915)	CODE: KTRI40431 MAINTENANCE KIT 500H (FOR 2017)		
