



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H31 VALUE

PRESSURE

130 ÷ 170
bar

FLOW RATE

500 ÷ 800
l/h

ABSORBED POWER

2,5 ÷ 4,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IPC TEMPERATURE STABILIZER - ATC



PW-H31
VALUE

PW-H31/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROL



CIRCULAR
DESIGN
& OPERATION



ALL
TERRAIN



MODERN
MODULAR
BUILD-UP



IPC
PUMP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



USER FRIENDLY ACCESS TO
ADJUSTMENT



STURDY AND LARGE TANK
AND ACCESSORIES STORAGE

TECHNICAL DATA

3 WHEELS		PW-H31 D1309P M	PW-H31 D1310P4 M	PW-H31 D1509P4 M	PW-H31 D1708P4 M	PW-H31 D1713P T
Code		IDAC41351	IDAC41352	IDAC41353	IDAC41354	IDAC41355
4 WHEELS		PW-H31/4 D1309P M	PW-H31/4 D1310P4 M	PW-H31/4 D1509P4 M	PW-H31/4 D1708P4 M	PW-H31/4 D1713P T
Code		IDAC41356	IDAC41357	IDAC41358	IDAC41359	IDAC41360
PERFORMANCE						
Operating pressure	bar/Mpa	30-130/3-13	30-130/3-13	30-150/3-15	30-170/4-17	30-170/3-17
Flow rate	l/h	280-540	300-600	300-540	300-500	400-800
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	3-400-50/9,1
Absorbed power	kW	2,5	2,7	2,7	2,7	4,7
Motor pole/rpm		2-2800	4-1400	4-1400	4-1400	2-2800
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	37,8	37,8	37,8	37,8	37,8
Fuel consumption	Kg/h	3,2	3,2	3,2	3,2	3,2
Fuel tank	l	18	18	18	18	18
Detergent tank	l	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	m	82x63x87	82x63x87	82x63x87	82x63x87	82x63x87
Weight	Kg	80	80	80	80	90

STANDARD EQUIPMENT

CODE: IPPR40031
HANDGRIP G4000
CERAMIC TECH



CODE: LCPR40013
EXTENSION P 70 -
HYPERJET 1/4F



CODE: UGLN49986
H.P. NOZZLE 1/4 1504 -
(FOR 1310/1713)



CODE: UGLN49985
H.P. NOZZLE 1/4 1504 -
(FOR 1509/1309)



CODE: UGLN75421
H.P. NOZZLE 1/4 15025 -
(FOR 1708)



CODE: TBAP40308
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 +
TPR255 Ø 0,4 - (FOR
1713/1310/1714)



CODE: LCPR40104
EXTENSION P70 + TPR255
Ø 0,35 - (FOR 1309/1509)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1309/1509/1708)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1713)




CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
LANCE FOR WASHING
FLOORS Ø 0,35



CODE: LCPR40214
EXTENSION P70 Ø 0,30
(FOR 1708)



CODE: KTRI40637
MAINTENANCE KIT 500H
(FOR 1309)



CODE: KTRI40638
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40641
MAINTENANCE KIT 500H
(FOR 1713)



CODE: KTRI40639
MAINTENANCE KIT 500H
(FOR 1509)



CODE: KTRI40640
MAINTENANCE KIT 500H
(FOR 1708)

